



Model ML60C-PDV

Multifunction dimmable LED Driver

Output with const. Current: 900-1750mA

Flicker-free and Built in DALI / 1-10V / PUSH dimming



Input Voltage	220-240VAC
Input Frequency	50-60 Hz
Input Current	0.45A max.
Output Current	900mA, 6-58VDC, 5.4-52.2W 1050mA, 6-58VDC, 6.3-60W 1200mA, 6-50VDC, 7.2-60W 1400mA, 6-43VDC, 8.4-60W 1750mA, 6-34VDC, 10.5-60W
Output Power	60W max.
Power Factor	≥ 0.90 (@240VAC, Full load and without dimmer)
Efficiency	≥85% (@240VAC, Full load and without dimmer)
Dimming Mode	DALI & 1-10V & PUSH dimming
Working Temperature (Ta)	-25°C~+50°C
Surface Temperature (Tc)	85°C max.
Lifetime	≥ 50000 hours (@Ta)
Isulation class	Class II, SELV
Protection class	IP20
Short circuit	Protection mode: Auto recovery
Safety	EN61347-1, EN61347-2-13, EN60598-1, EN60598-2-6
EMC	EN55015, EN61000-3-2 Class C, EN61000-3-3, EN61547
Approvals	SEMKO, CE

